



BLUSODA BOX

30
lt/h45
lt/hstainless
STEELDRY
COOLINGGAS
R290

fizz

BLUSODA BOX 30 FIZZ BLUSODA BOX 45 FIZZ

Cooling capacity (l/h)	30	45
Max continuous supply (l)	6	12
Cold water temperature*	5 - 12 °C	
Pump	Professional membrane carbonation pump	
Cooling technology	Aluminum fusion block - stainless steel coil	
Condensation	Forced ventilation	
Refrigerant gas	R290	
Adjustable thermostat	Yes	
Supply standard model	230 V - 50 Hz	
Supply 60 Hz model	-	220-230 V - 50/60 Hz
Compressor power	1/8 HP	1/5 HP
Absorbed power	210 W - 0,9 A	275 W - 1,2 A
Working room temperature	Min 16°C - Max 32°C	
Inlet water pipe	Ø5/16" (8 mm)	
Inlet CO ₂ pipe	Ø5/16" (8 mm)	
Typology	Undercounter	
Net weight (kg)	25	31
Gross weight (kg)	27	34
Dimensions W x D x H (mm)	260 x 416 x 416	318 x 440 x 468
Packaging dimensions (mm)	350 x 580 x 510	390 x 580 x 550


Dispensing options	Cold still water, cold sparkling water and room temperature water
Materials	Parts in robust stainless steel and aluminum

OPTIONAL



Water pressure reducer	
CO ₂ pressure reducer	
Filters	Activated carbon filter (inside)
Taps	Electronic or mechanical

* rated at a room temp. of 25 °C and inlet water temp. of 20 °C


For a proper installation of the system, the use of the WATER BLOCK is compulsory.



Blusoda Box 30



Blusoda Box 45



CERTIFICATIONS

